

7/21/2005

削除: 7/21/2005

削除: 7/18/20057/13/20057/13/20056/29/20056/29/20056/28/20056/28/20056/28/20056/27/2005

## 9.5 Port Type **wsag:AgreementState**

The purpose of this port type is to define a resource document type for monitoring the state of the agreement. This port type is not meant to be used as is but instead, its resource properties MAY be composed into a domain-specific Agreement port type.

コメント [作成者21]: Should we change the name?

削除: Running

書式変更: 箇条書きと段落番号

### 9.5.1 Resource Property **wsag:AgreementStateList**

The property exposes an **Agreement state** for the whole agreement as defined in section 7.1.

削除: 1

The set of values are:

- Pending
- Observed
- Rejected
- Complete

書式変更: フォント: 太字

書式変更: 箇条書きと段落番号

書式変更: フォント: 太字

書式変更: フォント: 太字

書式変更: フォント: 太字

The list has the following structure:

```
<wsag:AgreementStateList>
  <wsag:Pending termName="xs:string"> *
  ...
</wsag:Pending>
  <wsag:Observed termName="xs:string"> *
</wsag:Observed>
  <wsag:Rejected termName="xs:string"> *
  ...
</wsag:Rejected>
  <wsag:Complete termName="xs:string"> *
  ...
</wsag:Complete>
</wsag:ServiceTermStateList>
```

/wsag:AgreementStateList

List of agreement states indexed by name. The content in this list can appear in any order of Pending, Observed, Rejected and Complete.

/wsag:AgreementStateList/wsag:Pending

An agreement state which is in state pending.

/wsag:AgreementStateList/wsag:Observed

An agreement state which is in state observed.

/wsag:AgreementList/wsag:Rejected

An agreement state which is in state rejected

/wsag:AgreementList/wsag:Complete

An agreement state which is in state complete

書式変更: (言語 1) 日本語

書式変更: small