

1 GWD-R
2 OCCI-WG
3
4

Ralf Nyrén
Florian Feldhaus, GWDG
February 25, 2011
Updated: August 27, 2012

5 **Open Cloud Computing Interface - JSON Rendering**

6 Status of this Document

7 This document provides information to the community regarding the specification of the Open Cloud Computing Interface. Distribution is unlimited.

9 Copyright Notice

10 Copyright ©Open Grid Forum (2012). All Rights Reserved.

11 Trademarks

12 OCCI is a trademark of the Open Grid Forum.

13 Abstract

14 This document, part of a document series, produced by the OCCI working group within the Open Grid Forum (OGF), provides a high-level definition of a Protocol and API. The document is based upon previously gathered requirements and focuses on the scope of important capabilities required to support modern service offerings.

17 Comments

18 **Contents**

19	1 Introduction	3
20	2 Notational Conventions	3
21	3 OCCI JSON Rendering	3
22	4 JSON Format	4
23	4.1 Attributes	4
24	4.2 Resource Instance Format	4
25	4.3 Link Instance Format	4
26	4.4 Action Format	5
27	4.5 Kind Format	6
28	4.6 Mixin Format	6
29	4.7 Action Category Format	7
30	4.8 Attribute Description Format	7
31	5 Detailed Examples	8
32	5.1 Resource Instance Format Example	8
33	5.2 Link Instance Format Example	9
34	5.3 Action Instance Format Example	9
35	5.4 Kind Format Example	9
36	5.5 Mixin Format Example	10
37	5.6 Action Category Format Example	11
38	6 Glossary	12
39	7 Contributors	12
40	8 Intellectual Property Statement	14
41	9 Disclaimer	14
42	10 Full Copyright Notice	14

1 Introduction

The Open Cloud Computing Interface (OCCI) is a RESTful Protocol and API for all kinds of management tasks. OCCI was originally initiated to create a remote management API for IaaS¹ model-based services, allowing for the development of interoperable tools for common tasks including deployment, autonomic scaling and monitoring. It has since evolved into a flexible API with a strong focus on interoperability while still offering a high degree of extensibility. The current release of the Open Cloud Computing Interface is suitable to serve many other models in addition to IaaS, including PaaS and SaaS.

In order to be modular and extensible the current OCCI specification is released as a suite of complimentary documents, which together form the complete specification. The documents are divided into three categories consisting of the OCCI Core, the OCCI Renderings and the OCCI Extensions.

- The OCCI Core specification consists of a single document defining the OCCI Core Model. The OCCI Core Model can be interacted with *renderings* (including associated behaviours) and expanded through *extensions*.
- The OCCI Rendering specifications consist of multiple documents each describing a particular rendering of the OCCI Core Model. Multiple renderings can interact with the same instance of the OCCI Core Model and will automatically support any additions to the model which follow the extension rules defined in OCCI Core.
- The OCCI Extension specifications consist of multiple documents each describing a particular extension of the OCCI Core Model. The extension documents describe additions to the OCCI Core Model defined within the OCCI specification suite. They do not require changes to the HTTP Rendering specifications as of this version of the specification.

The current specification consists of three documents. This specification describes version 1.1 of OCCI. Future releases of OCCI may include additional rendering and extension specifications. The documents of the current OCCI specification suite are:

OCCI Core describes the formal definition of the the OCCI Core Model [1].

OCCI HTTP Rendering defines how to interact with the OCCI Core Model using the RESTful OCCI API [2]. The document defines how the OCCI Core Model can be communicated and thus serialised using the HTTP protocol.

OCCI Infrastructure contains the definition of the OCCI Infrastructure extension for the IaaS domain [3]. The document defines additional resource types, their attributes and the actions that can be taken on each resource type.

2 Notational Conventions

All these parts and the information within are mandatory for implementors (unless otherwise specified). The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [4].

3 OCCI JSON Rendering

The OCCI JSON Rendering specifies a rendering of OCCI instance types in the JSON data interchange format as defined in [5].

¹Infrastructure as a Service

82 The Rendering can be used to render OCCI instances independently of the transport mechanism being used.
83 Thus messages can be delivered by e.g. the HTTP protocol as specified in [2] or by using text files with the
84 .json file extension as defined in [5].

85 The following media-type MUST be used for the OCCI JSON Rendering:

86 application/occi+json

87 4 JSON Format

88 The OCCI JSON Rendering consists of a JSON object containing information on the OCCI Core instances
89 OCCI Kind, OCCI Mixin, OCCI Action Category, OCCI Action, OCCI Link and OCCI Resource. The rendering
90 of each OCCI Core instance will be described in the following sections.

91 4.1 Attributes

92 Attribute names consist of alphanumeric characters separated by dots. The dots define a namespace hierarchy.
93 This hierarchy is reflected by stacked JSON objects as shown in the following example. The last object contains
94 either a Number, String or Boolean value or, when used within a category, an Object following the Attribute
95 Description Format (see 4.8).

```
96 {  
97   "one": {  
98     "two": {  
99       "three": Number | String | Boolean | Object  
100     }  
101   }  
102 }
```

103 4.2 Resource Instance Format

104 The OCCI Resource instance format consists of a JSON object as shown in the following example. Section
105 5.1 contains a detailed example. Table 1 defines the object members.

```
106 {  
107   "resources": [  
108     {  
109       "kind": String ,  
110       "mixins": Array ,  
111       "attributes": Object ,  
112       "action_categories": Array ,  
113       "id": String ,  
114       "links": Array  
115     }  
116   ]  
117 }
```

118 4.3 Link Instance Format

119 The OCCI Link instance format consists of a JSON object as shown in the following example. Section 5.2
120 contains a detailed example. Table 2 defines the object members.

Table 1. OCCI Resource instances are rendered inside the top-level JSON object with name *resources* as an array of JSON objects with the following entries:

Object member	JSON type	Description	Mutability	Multiplicity
kind	String	Type identifier	immutable	1
mixins	Array of Strings	List of type identifiers of associated OCCI Mixins	mutable	0..*
attributes	Object	Instance Attributes (see 4.8)	mutable	0..*
action_categories	Array of Strings	List of type identifiers of OCCI Action Categories applicable to the OCCI Resource instance	mutable	0..*
id	String	URN representing the UUID [6] of the OCCI Resource	immutable	1
links	Array of Strings	List of URNs representing the UUID [6] of an OCCI Link	mutable	0..*

```

121 {
122   "links": [
123     {
124       "kind": String,
125       "mixins": Array,
126       "attributes": Object,
127       "action_categories": Array,
128       "id": String,
129       "source": String,
130       "target": String,
131       "rel": String
132     }
133   ]
134 }
```

Table 2. OCCI Link instances are rendered inside the top-level JSON object with name *links* as an array of JSON objects with the following entries:

Object member	JSON type	Description	Mutability	Multiplicity
kind	String	Type identifier	immutable	1
mixins	Array of Strings	List of type identifiers of associated OCCI Mixins	mutable	0..*
attributes	Object	Instance attributes (see 4.8)	mutable	0..*
action_categories	Array of Strings	List of type identifiers of OCCI Action Categories applicable to the OCCI Link instance	mutable	0..*
id	String	URN representing the UUID [6] of the OCCI Link	immutable	1
source	String	URN representing the UUID [6] of the source OCCI Resource	immutable	1
target	String	URN representing the UUID [6] of the target Resource if the target is an OCCI Resource. URI representing an external Resource otherwise.	immutable	1
rel	string	Type identifier of the target Resource. MUST be supplied if the target is an OCCI Resource.	immutable	0..1

135 4.4 Action Format

136 To trigger an OCCI Action a representation of the OCCI Action is needed. This representation includes all
 137 information to carry out the OCCI Action on an OCCI Entity.

138 The OCCI Action instance format consists of a JSON object as shown in the following example. Section 5.6
 139 contains a detailed example. Table 3 defines the object members.

```

140 {
141   "action": {
142     "action_category": String,
143     "attributes": Object,
144   }
```

145 }

Table 3. OCCI Action instances are rendered inside the top-level JSON object with name *action* as a JSON objects with the following entries:

Object member	JSON type	Description	Mutability	Multiplicity
action_category	String	Type identifier	immutable	1
attributes	Object	Instance attributes (see 4.8)	mutable	0..*

146

4.5 Kind Format

147 The OCCI Kind instance format consists of a JSON object as shown in the following example. Section 5.4
148 contains a detailed example. Table 4 defines the top-level object members.

Table 4. OCCI Kind instances are rendered inside the top-level JSON object with name *kinds* as an array of JSON objects with the following entries:

Object member	JSON type	Description	Mutability	Multiplicity
term	String	Unique identifier within the categorisation scheme	immutable	1
scheme	String	Categorisation scheme	immutable	1
title	String	Title of the OCCI Kind	immutable	0..1
attributes	Object	Attribute description, see 7	immutable	0..*
related	Array of Strings	List of type identifiers containing only the related "parent" Kind instance	immutable	0..1
action_categories	Array of Strings	List of OCCI Action Category type identifiers	immutable	0..*
location	string	Transport protocol specific URI bound to the OCCI Kind instance. MUST be supplied for the OCCI Kinds of all OCCI Entities except OCCI Entity itself	immutable	0..1

```

149 {
150   "kinds": [
151     {
152       "term": String,
153       "scheme": String,
154       "title": String,
155       "attributes": Object,
156       "action_categories": Array,
157       "related": Array,
158       "location": String
159     }
160   ]
161 }
```

162

4.6 Mixin Format

163 The OCCI Mixin format consists of a JSON object as shown in the following example. Section 5.5 contains
164 a detailed example. Table 5 defines the top-level object members.

```

165 {
166   "mixins": [
167     {
168       "term": String,
169       "scheme": String,
170       "title": String,
```

Table 5. OCCI Mixin instances are rendered inside the top-level JSON object with name *mixins* as an array of JSON objects with the following entries:

Object member	JSON type	Description	Mutability	Multiplicity
term	String	Unique identifier within the categorisation scheme	immutable	1
scheme	String	Categorisation scheme	immutable	1
title	String	Title of the OCCI Mixin	immutable	0..1
attributes	Object	Attribute description, see 7	immutable	0..*
related	Array of Strings	List of type identifiers of the related "parent" Mixin instances	immutable	0..*
action_categories	Array of Strings	List of OCCI Action type identifiers	immutable	0..*
location	String	Transport protocol specific URI bound to the OCCI Mixin instance	immutable	1

```

171         "attributes": Object,
172         "action_categories": Array,
173         "related": Array,
174         "location": String
175     }
176 ]
177 }

```

4.7 Action Category Format

An OCCI Category is used to describe an OCCI Action.

The OCCI Action Category format consists of a JSON object as shown in the following example. Table 6 defines the top-level object members.

Table 6. OCCI Categories describing OCCI Actions instances are rendered inside the top-level JSON object with name *actions* as an array of JSON Objects with the following entries:

Object member	JSON type	Description	Mutability	Multiplicity
term	String	Unique type identifier within the categorisation scheme	immutable	1
scheme	String	Categorisation scheme	immutable	1
title	String	Title of the OCCI Action	immutable	0..1
attributes	Object	Attribute description, see 7	immutable	0..*

```

182 {
183     "action_categories": [
184         {
185             "term": String,
186             "scheme": String,
187             "title": String,
188             "attributes": Object,
189         }
190     ]
191 }

```

4.8 Attribute Description Format

OCCI Attribute Descriptions are rendered as JSON objects as defined in table 7

```

194 {
195     "mutable": Boolean,

```

Table 7. All OCCI Attribute Definition properties are optional, but may contain defaults which MUST be used if the Attribute is not present in the instantiated OCCI Entity.

Object member	JSON type	Description	Default
mutable	Boolean	Defines if the Attribute is mutable after initialization	false
required	Boolean	Defines if the Attribute MUST be specified at instantiation of the OCCI Entity	false
type	String	Type of the Attribute. MUST be either string, number or boolean.	string
default	String, Number or Boolean	Attribute default. MUST be the same type as defined in the type property and MUST be used if the Attribute is not present in the instantiated OCCI Entity	
description	String	Description of the attribute	

```

196     "required": Boolean,
197     "type": String,
198     "default": String | Number | Boolean,
199     "description": String
200 }

```

5 Detailed Examples

5.1 Resource Instance Format Example

```

203 {
204   "resources": [
205     {
206       "kind": "http://schemas.ogf.org/occi/infrastructure#compute",
207       "mixins": [
208         "http://example.com/occi/templates#my_os_mixin"
209       ],
210       "attributes": {
211         "occi": {
212           "compute": {
213             "speed": 2,
214             "memory": 4,
215             "cores": 2
216           }
217         },
218         "com": {
219           "example": {
220             "occi": {
221               "templates": {
222                 "my_os_mixin": {
223                   "my_attribute": "my_value"
224                 }
225               }
226             }
227           }
228         }
229       },
230       "action_categories": [
231         "http://schemas.ogf.org/occi/infrastructure/compute/action#start"
232       ],

```



```

233         "id": "urn:uuid:996ad860-2a9a-504f-8861-aeafd0b2ae29",
234         "links": [
235             "urn:uuid:22fe83ae-a20f-54fc-b436-cec85c94c5e8"
236         ]
237     }
238 ]
239 }

```

240 5.2 Link Instance Format Example

```

241 {
242     "links": [
243         {
244             "kind": "http://schemas.ogf.org/occi/infrastructure#networkinterface",
245             "mixins": [
246                 "http://schemas.ogf.org/occi/infrastructure/networkinterface#ipnetworki
247             ],
248             "attributes": {
249                 "occi": {
250                     "infrastructure": {
251                         "networkinterface": {
252                             "interface": "eth0",
253                             "mac": "00:80:41:ae:fd:7e",
254                             "address": "192.168.0.100",
255                             "gateway": "192.168.0.1",
256                             "allocation": "dynamic"
257                         }
258                     }
259                 }
260             },
261             "action_categories": [
262                 "http://schemas.ogf.org/occi/infrastructure/networkinterface/action#up"
263             ],
264             "id": "urn:uuid:22fe83ae-a20f-54fc-b436-cec85c94c5e8",
265             "target": "urn:uuid:b7d55bf4-7057-5113-85c8-141871bf7635",
266             "source": "urn:uuid:996ad860-2a9a-504f-8861-aeafd0b2ae29"
267         }
268     ]
269 }

```

270 5.3 Action Instance Format Example

```

271 {
272     "action": {
273         "action_category": "http://schemas.ogf.org/occi/infrastructure/compute/action#st
274         "attributes": {
275             "method": "graceful"
276         }
277     }
278 }

```

279 5.4 Kind Format Example

```

280 {
281     "kinds": [
282         {

```

```

283     "term": "compute",
284     "scheme": "http://schemas.ogf.org/occi/infrastructure#",
285     "title": "Compute Resource",
286     "related": [
287         "http://schemas.ogf.org/occi/core#resource"
288     ],
289     "attributes": {
290         "occi": {
291             "compute": {
292                 "hostname": {
293                     "mutable": true,
294                     "required": false,
295                     "type": "string",
296                     "description": "Hostname of the compute resource"
297                 },
298                 "state": {
299                     "mutable": false,
300                     "required": false,
301                     "type": "string",
302                     "default": "inactive",
303                     "description": "State the compute resource is in"
304                 }
305             }
306         }
307     },
308     "action_categories": [
309         "http://schemas.ogf.org/occi/infrastructure/compute/action#start",
310         "http://schemas.ogf.org/occi/infrastructure/compute/action#stop",
311         "http://schemas.ogf.org/occi/infrastructure/compute/action#restart",
312         "http://schemas.ogf.org/occi/infrastructure/compute/action#suspend"
313     ],
314     "location": "/compute/"
315 }
316 ]
317 }

```

5.5 Mixin Format Example

```

319 {
320     "mixins": [
321         {
322             "term": "medium",
323             "scheme": "http://example.com/template/resource#",
324             "related": [
325                 "http://schemas.ogf.org/occi/infrastructure#resource_tpl"
326             ],
327             "attributes": {
328                 "occi": {
329                     "compute": {
330                         "speed": {
331                             "type": "number",
332                             "default": 2.8
333                         }
334                     }
335                 }
336             },

```

```
337         "title": "Medium VM",
338         "location": "/template/resource/medium/"
339     }
340 ]
341 }
```

342 5.6 Action Category Format Example

```
343 {
344     "action_categories": [
345         {
346             "term": "stop",
347             "scheme": "http://schemas.ogf.org/occi/infrastructure/compute/action#",
348             "title": "Stop Compute instance",
349             "attributes": {
350                 "method": {
351                     "mutable": true,
352                     "required": false,
353                     "type": "string",
354                     "default": "poweroff"
355                 }
356             }
357         }
358     ]
359 }
```

360 6 Glossary

Term	Description
Action	An OCCI base type. Represent an invocable operation on a Entity sub-type instance or collection thereof.
Category	A type in the OCCI model. The parent type of Kind.
Client	An OCCI client.
Collection	A set of Entity sub-type instances all associated to a particular Kind or Mixin instance.
Entity	An OCCI base type. The parent type of Resource and Link.
Kind	A type in the OCCI model. A core component of the OCCI classification system.
Link	An OCCI base type. A Link instance associate one Resource instance with another.
mixin	An instance of the Mixin type associated with a resource instance . The “mixin” concept as used by OCCI <i>only</i> applies to instances, never to Entity types.
Mixin	A type in the OCCI model. A core component of the OCCI classification system.
OCCI	Open Cloud Computing Interface.
361 OCCI base type	One of Entity, Resource, Link or Action.
OGF	Open Grid Forum.
Resource	An OCCI base type. The parent type for all domain-specific resource types.
resource instance	An instance of a sub-type of Entity. The OCCI model defines two sub-types of Entity, the Resource type and the Link type. However, the term <i>resource instance</i> is defined to include any instance of a <i>sub-type</i> of Resource or Link as well.
Tag	A Mixin instance with no attributes or actions defined.
Template	A Mixin instance which if associated at resource instantiation time pre-populate certain attributes.
type	One of the types defined by the OCCI model. The OCCI model types are Category, Kind, Mixin, Action, Entity, Resource and Link.
concrete type/sub-type	A concrete type/sub-type is a type that can be instantiated.
URI	Uniform Resource Identifier.
URL	Uniform Resource Locator.
362 URN	Uniform Resource Name.

363 7 Contributors

³⁶⁴ We would like to thank the following people who contributed to this document:

Name	Affiliation	Contact
Michael Behrens	R2AD	behrens.cloud at r2ad.com
Mark Carlson	Oracle	mark.carlson at oracle.com
Andy Edmonds	Intel - SLA@SOI project	andy at edmonds.be
Sam Johnston	Google	samj at samj.net
Gary Mazzaferro	OCCI Counsellor - AlloyCloud, Inc.	garymazzaferro at gmail.com
³⁶⁵ Thijs Metsch	Platform Computing, Sun Microsystems	tmetsch at platform.com
Ralf Nyrén	Aurenav	ralf at nyren.net
Alexander Papaspyrou	TU Dortmund University	alexander.papaspyrou at tu-dortmund.de
Alexis Richardson	RabbitMQ	alexis at rabbitmq.com
Shlomo Swidler	Orchestratus	shlomo.swidler at orchestratus.com
Florian Feldhaus	GWDG	florian.feldhaus at gwdg.com

³⁶⁶ Next to these individual contributions we value the contributions from the OCCI working group.

367 **8 Intellectual Property Statement**

368 The OGF takes no position regarding the validity or scope of any intellectual property or other rights that
369 might be claimed to pertain to the implementation or use of the technology described in this document or the
370 extent to which any license under such rights might or might not be available; neither does it represent that
371 it has made any effort to identify any such rights. Copies of claims of rights made available for publication
372 and any assurances of licenses to be made available, or the result of an attempt made to obtain a general
373 license or permission for the use of such proprietary rights by implementers or users of this specification can
374 be obtained from the OGF Secretariat.

375 The OGF invites any interested party to bring to its attention any copyrights, patents or patent applications,
376 or other proprietary rights which may cover technology that may be required to practice this recommendation.
377 Please address the information to the OGF Executive Director.

378 **9 Disclaimer**

379 This document and the information contained herein is provided on an “As Is” basis and the OGF disclaims all
380 warranties, express or implied, including but not limited to any warranty that the use of the information herein
381 will not infringe any rights or any implied warranties of merchantability or fitness for a particular purpose.

382 **10 Full Copyright Notice**

383 Copyright © Open Grid Forum (2009-2011). All Rights Reserved.

384 This document and translations of it may be copied and furnished to others, and derivative works that comment
385 on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in
386 whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph
387 are included on all such copies and derivative works. However, this document itself may not be modified in
388 any way, such as by removing the copyright notice or references to the OGF or other organizations, except
389 as needed for the purpose of developing Grid Recommendations in which case the procedures for copyrights
390 defined in the OGF Document process must be followed, or as required to translate it into languages other
391 than English.

392 The limited permissions granted above are perpetual and will not be revoked by the OGF or its successors or
393 assignees.

394 **References**

395 [1] R. Nyrén, A. Edmonds, A. Papaspyrou, and T. Metsch, “Open Cloud Computing Interface – Core,”
396 GFD-P-R.183, April 2011. [Online]. Available: <http://ogf.org/documents/GFD.183.pdf>

397 [2] T. Metsch and A. Edmonds, “Open Cloud Computing Interface – HTTP Rendering,” GFD-P-R.185,
398 April 2011. [Online]. Available: <http://ogf.org/documents/GFD.185.pdf>

399 [3] —, “Open Cloud Computing Interface – Infrastructure,” GFD-P-R.184, April 2011. [Online]. Available:
400 <http://ogf.org/documents/GFD.184.pdf>

401 [4] S. Bradner, “Key words for use in RFCs to Indicate Requirement Levels,” RFC 2119
402 (Best Current Practice), Internet Engineering Task Force, Mar. 1997. [Online]. Available:
403 <http://www.ietf.org/rfc/rfc2119.txt>

404 [5] D. Crockford, “The application/json Media Type for JavaScript Object Notation (JSON),”
405 RFC 4627 (Informational), Internet Engineering Task Force, Jul. 2006. [Online]. Available:
406 <http://www.ietf.org/rfc/rfc4627.txt>

- 407 [6] P. Leach, M. Mealling, and R. Salz, "A Universally Unique Identifier (UUID) URN Namespace,"
408 RFC 4122 (Proposed Standard), Internet Engineering Task Force, Jul. 2005. [Online]. Available:
409 <http://www.ietf.org/rfc/rfc4122.txt>